

DOGHOUSE 4.0

INSTALLATION AND CHARGING INSTRUCTIONS

Installation Instructions:

1. Carefully hold up the charging rack into location and level. Mark the top two screw hole locations with pencil.
2. Install the two screws. Make sure that there is proper support.
3. Hang the Doghouse onto the two screws.
4. Screw rest of the rack into wall with anchor screws (no pre-drilling required) checking to make sure that it is level.
5. Plug power cord into DogHouse and neatly run the cord to the AC outlet. Secure the cord to wall.
6. Unpack all of your Soundogs and test for proper operation and set into the charging station
7. Save two of the Soundog white boxes for future shipping.
8. Pack up all packaging and discard.



KIT CONTENTS:

6 Anchor Screws

TOOLS NEEDED:

Pencil Level Measuring Tape
Phillips screwdriver or cordless drill

REMEMBER:
Plug charger power cord
into charger before plugging
into a wall outlet.

Charging Instructions:

A Soundog holds up to a 16-hour charge. Simply place the Soundogs in charging tray nightly. It will take three charges to acquire full charge capacity of the nickel metal hydride battery. Average time to charge a depleted Soundog is eight hours.

Cleaning Instructions:

Use warm damp cloth with same cleaning supplies used to clean stainless steel surfaces to keep the trays clean. Wipe out all dirt. The trays should be wiped down monthly.

DogHouse Specifications:

Input Power: 100-240 VAC, 47-63 Hz current regulator charger
Output Power: Rated 5.8VDC, 165 mA; current regulated
Power Consumption: 12 Watts
Size: 14.75"W x 28"H x 7.75"D; Weight: 14.25lbs
Battery: 4x1650 mAh Ni-mH
DC No Load: 11.5VDC
LED Indication: Yellow LED on when battery connected and Charging.
Specification subject to change without notice.



SOUNDog[®]

For installation information, please call 231.237.0842

SPROX[®]

DESIGNED AND MANUFACTURED IN THE USA

www.sproxusa.com