

# SOUNDDOG® 4.0

## EIGHT CHANNEL SOUNDDOG RECEIVER SPECIFICATIONS

### Sounddog Specifications:

- Channels: 8 preset frequencies
  - Buttons: LED's indicate channel selected (1-million button presses)
  - Frequency Range: FM 72.0 to 76.0 MHz
  - RF Sensitivity: 22 dB nominal
  - Antenna: Internal on bottom housing
  - FCC Compliance: Part 15
  - Audio Response: 450-15,000Hz
  - Output Level: max ~98dB
  - Speaker: 4" Neodymium\_4 Ohm\_10W
  - Headphone Jack: Stereo\_2 watt\_3.5 mm female jack
  - Battery: 14 Hr Playback\_NiMH\_1600mAh
  - Battery Life: 1,000 charges\_no memory (3 yr. life expectancy)
  - Battery Charger: Use only Sounddog 4.0 certified chargers to avoid damage
  - Housing: Black High Impact Polycarbonate
  - Labels: Sounddog standard logo PVC industrial strength  
(custom labels and wraps available)
  - Dimensions: 130mm W x 144mm H x 124.8mm D
  - Weight: 1.6 Lbs
- Specification subject to change without notice.



For sales and installation information  
please call 231.237.0842

SPROX®

DESIGNED IN THE USA - MANUFACTURED IN CHINA

[www.sproxusa.com](http://www.sproxusa.com)